






VALVE HEAD I40 TYPE Q PTFE





ART. NO. 315543

GENERAL

-  The KEOFITT CLASSIC "INGOLD" Sampling Valve owes its hygienic design and one-piece construction to the original KEOFITT valve. For 40 MM Ingold ports.
-  The product to be sampled should have a maximum viscosity of 0-1.000 cP and should not contain particles larger than 2 mm diameter.
-  The valve can be sterilized by means of SIP (EHEDG test) and cleaned by means of CIP (EHEDG certified). Suited for autoclave.
-  The sampling valve can be used for any process sampling for microbiological, chemical and/or physical analysis.



FEATURES

-  Installation: 40 mm Ingold port
-  Operation: Lever handle
-  Inlet / Outlet: Depending on choice of valve body
-  Membrane: PTFE (TFM 1600 - white)

CERTIFICATION*

· Conforms to 3-A · EHEDG CIP · 3.1 Material Certificate · EU 1935/2004

TECHNICAL DATA

Material (product contact)

· Membrane PTFE (TFM 1600 - white)

Material (without product contact)

· Steel parts AISI 303L (1.4305)
· Steel parts AISI 316L (1.4404)
· Lever handle AISI 316 (1.4404)

Membrane

· Article PTFE, WHITE (# 310055)
· Certification* FDA · USP · EU 1935/2004

Pressure & Temperature




· Pressure 0 - 6 bar (g) / 0 - 87 psi (g)
· Temperature 1 - 150 °C / 34 - 302 ° F
· Air supply -





Net Weight

· Kg/lbs 0,371 kg / 0,82 lbs

Spareparts

773141PTFE SPARE PARTS FOR I 40 MM HEAD 315541/43



Hose Piece	Standard for 40 mm port length	Standard for 52 mm port length	
Mini Tri-Clamp	<p>Not available</p>  <p>310002</p>	<p>Not available</p>  <p>320002</p>	<p>Not available</p>  <p>320005</p>
Welding liner	<p>On request</p>	<p>On request</p>	<p>On request</p>
	<p>On request</p>	<p>On request</p>	<p>On request</p>  <p>320007</p>