



VALVE BODY TYPE 152, TC/TC

ART. NO. 320005

GENERAL



The KEOFITT CLASSIC "INGOLD" Sampling Valve owes its hygienic design and one-piece construction to the original KEOFITT valve. For 52 MM Ingold ports. Unique serial number engraved in each valve ("E" = internal electro polish).


Designed for sampling of liquids with a viscosity of up to approx. 1.000 cP containing no particles larger than Ø2 mm. Sampling of more viscous liquids is possible, only will it take longer (depending on process pressure).



Cleaning/sterilizing: Between batches: Valve in open position: Cleanable by means of CIP using the detergent solution suitable for the actual process media (EHEDG certificate available). Between samples: Valve in its normal closed position: cleanable by CIP as "Between batches" or the valve may be sterilized by means of steam SIP (EHEDG test report available) or chemical SIP using a procedure appropriate to the actual circumstances. For further advice, please contact Keofitt.

The sampling valve can be used for any process sampling for microbiological, chemical and/or physical analysis.

FEATURES



CERTIFICATION*

· EHEDG CIP · 3.1 Material Certificate · EU 1935/2004 · Ra Cert. incl. measurements

TECHNICAL DATA

Material (product contact)

AISI 316L (1.4435 BNII) · Steel parts Silicone (FDA · EU 1935/2004) O-ring

Material (without product contact)

· Steel parts

AISI 316L (1.4435 BNII)

Surface Treatment

 Outside · Inside (wetted surface) · Process connection

Electropolished Ra <= 1.2 µm Ra <= 0.2 µm Electropolished Ra <= 0.2 µm


Depending on choice of valve head

Pressure & Temperature

- · Pressure · Temperature
- Air supply

Depending on choice of valve head

Net Weight







Operation: Depending on choice of valve head

Membrane: Depending on choice of valve head

*For further information and download please visit keofitt.dk

G 1 1/4

