

10 PACK O-RING 5,3 x 2,4 EPDM/FDA

ART. NO. 400830E


GENERAL



KEOFITT has the widest selection of spare parts and accessories to complete your sampling system



O-ring is included in various products - see backside for further details



CERTIFICATION*

· FDA §177.2600 · USP Class VI · EU 1935/2004

TECHNICAL DATA

Material type:	Peroxide cured, Ethylene Propylene Terpolymer 70shA
Color:	Light grey
Temperature Range:	-40°C - +150°C / -40°F - +302°
Storage recommendation:	According to ISO 2230
Hardness, Shore A (pts):	75
Tensile strength (MPa):	11
Ultimate Elongation (%):	585
Compression set, DIN 53517, 22h/150°C (%):	25

Net Weight

· Kg/lbs 0,001 kg /0,002 lbs

EPDM O-RING TO REPLACE STANDARD SILICONE O-RING PART OF

Part of valve body

600048	VALVE HEAD W9 TYPE H W/MICRO PORT
600048E	VALVE HEAD W9 TYPE H/ MICRO EPDM
600049	VALVE HEAD W9 TYPE K W/MICRO PORT
600049E	VALVE HEAD W9 TYPE K W/MICRO PORT EPDM

Part of kit

772001	PARTS FOR CARLSBERG FLASK 200001
772002	PARTS FOR NEW CARLSBERG FLASK
772601	PARTS FOR OLD ASEPTICK SYSTEM 260001
775500	PARTS FOR STEAM BOILER 550000
776048	PARTS FOR W9 HEAD 600048/49
776048EPDM	PARTS FOR W9 HEAD 600048E/49E

Part of fitting

400013	M4 QC SPIKE BAG HOLDER
400058	SAMPLING COIL M4
400061	QUICK COUPLING PLUG M4
400070	QUICK COUPLING M4 FOR STEEL PIPE
400071	QUICK COUPLING M4 FOR PTFE
400082	QC M4 F/ HOSE I.D. 3,1 MM
400083	QUICK COUPLING M4 MINI TC
400084	QUICK COUPLING M4 F/I.D. 4 MM
400085	QUICK COUPLING M4 F/ O.D. 13,5/I.D. 5 MM
400086	QUICK COUPLING M4 W/W9 HOSE PIECE
550002	PTFE TUBING W/ QUICK COUPLING 0,5 M
550002.2	PTFE TUBING W/QUICK COUPLING/TC 0,5 M
550003	PTFE TUBING W/ QUICK COUPLING 1 M
550003.2	PTFE TUBING W/QUICK COUPLING/TC 1m