





## VALVE HEAD W9 TYPE H, EPDM

ART. NO. 600041E

### GENERAL

-  The KEOFITT CLASSIC W9 Sampling Valve is the original and leading sterilizable sampling valve in the world market. Used across all industries from breweries to bio-pharm for decades. More than 320 standard valve configurations available.
-  The product to be sampled should have a maximum viscosity of 0-1.000 cP and should not contain particles larger than 2 mm diameter
-  The valve can be cleaned by means of SIP and/or CIP through the open valve seat
-  The sampling valve can be used for any process sampling for microbiological, chemical and/or physical analysis

### FEATURES

-  Installation: Depending on choice of valve body
-  Operation: Turn knob (open right)
-  Inlet / Outlet: Depending on choice of valve body
-  Membrane: EPDM (PTFE & Silicone available)

### CERTIFICATION

- Conform to 3-A · EHEDG CIP · EU 1935/2004

### TECHNICAL DATA

#### Material (product contact)

- Membrane EPDM

#### Material (without product contact)

- Steel parts AISI 303L (1.4305)
- Steel parts AISI 316L (1.4404)
- Knob HDPE (black)

#### Surface Treatment

- Outer Surface Electropolished

#### Pressure & Temperature

- Pressure 0 - 6 bar (g) / 0 - 87 psi (g)
- Temperature 1 - 130° C / 34 - 266° F

#### Net Weight

- Kg/lbs 0,224 kg / 0,49 lbs

#### Spareparts

- 776041EPDM SPARE PARTS W9 HEAD 60041E/42E/43E/47E

