



SIMPLEX VALVE TYPE C1"/N, EPDM

ART. NO. 832244EPDM

GENERAL

- The KEOFITT SIMPLEX Sampling Valve is KEOFITT's low-cost CIP-able sampling valve for less demanding applications. Typically used replacing existing non-hygienic sampling cocks. More than 20 different configurations available.
- The sampling valve can be used for any process sampling for chemical and/or physical analysis
- The valve can be cleaned by means of CIP through the open valve seat
- The product to be sampled should have a maximum viscosity of 0-1.000 cP and should not contain particles larger than 2 mm diameter

FEATURES

- Installation: Clamp connection 1" N/A (DIN)
- Operation: Pneumatically operated
- Outlet: Hose piece - other types are available as accessories
- Membrane: EPDM (PTFE & Silicone available)

CERTIFICATION

- Conform to 3-A · EHEDG CIP · 3.1 Material Certificate · EU 1935/2004

TECHNICAL DATA

Material (product contact)

· Steel parts	AISI 316L (1.4404)
· Membrane	EPDM
· O-ring	Silicone

Material (without product contact)

· Steel parts	AISI 316L (1.4404)
· Steel parts	AISI 303L (1.4305)

Surface Treatment

· Outer Surface	Machined
· Inner Surface	$\leq Ra 0.8 \mu m$

Pressure & Temperature



· Pressure	0 - 6 bar (g) / 0 - 87 psi (g)
· Temperature	1 - 130°C / 34 - 266°F
· Air Supply	4 - 6 bar (g) / 58 - 87 psi (g)

Net Weight

· Kg/lbs	0,706 kg / 1,56 lbs
----------	---------------------

Spareparts

300119	O-ring
550170	Screw for air fitting
550184	O-ring
600052	Membrane
600839	Swivel elbow for aircylinder
800830	O-ring
830149	Bushing
830825	O-ring



Parts & Accessories for Simplex™

KEOFIT SIMPLEX™