






SESAME VALVE TYPE T

ART. NO. 890001

GENERAL

-  The KEOFITT SESAME Sampling Valve is our patented double-seat sampling valve. Unique in the market, it eliminates dead-leg during sampling while incorporating steam supply control. Unique serial no. for each valve ("E" = internal electro polish).
-  Designed for sampling of liquids with a viscosity of up to approx. 1.000 cP containing no particles larger than Ø2 mm. Sampling of more viscous liquids is possible, only will it take longer (depending on process pressure).
-  Cleaning/sterilizing: Between batches: Valve in open position: Cleanable by means of CIP using the detergent solution suitable for the actual process media (EHEDG certificate available). Between samples: Valve in its normal closed position: cleanable by CIP as "Between batches" or the valve may be sterilized by means of steam SIP (EHEDG test report available) or chemical SIP using a procedure appropriate to the actual circumstances. For further advice, please contact Keofitt.
-  The sampling valve can be used for any process sampling for chemical and/or physical analysis.



FEATURES

-  Installation: Tank welding
-  Operation: Depending on choice of valve head
-  Outlet: Hose piece
-  Membrane: Depending on choice of valve head

CERTIFICATION*

· Conforms to 3-A · EHEDG CIP · 3.1 Material Certificate · EU 1935/2004 · Ra Cert. incl. measurements

TECHNICAL DATA

Material (product contact)

· Steel parts AISI 316L (1.4435 BNII)

Material (without product contact)

· Steel parts AISI 316L (1.4404)
· Steel parts AISI 304 (1.4301)
· Lever handle AISI 316 (1.4404)

Surface Treatment

· Outside Electropolished Ra <= 1.2 µm
· Inside (wetted surface) Ra <= 0.5 µm
· Process connection Ra <= 0.5 µm

Pressure & Temperature

· Pressure Operation: Depending on choice of valve head
· Temperature Operation: Depending on choice of valve head
· Air supply Operation: Depending on choice of valve head

Net Weight

· Kg/lbs 0,623 kg /0,00 lbs

